

# **Instruction Manual**

**Oscar 3-Wheeler**

**Otis 4-Wheeler**

PLEASE RETAIN FOR FUTURE REFERENCE

## **ATTENTION**

Please read this instruction manual carefully before using the stroller. The instructions apply to both the Oscar and the Otis models unless otherwise specified.

The stroller seat unit is suitable from newborn to 17kgs in weight.

The carry cot is suitable from newborn to 9kgs or when the child can sit up unaided, whichever is first.

## **WARNING**

Always follow these instructions.

Always apply the parking brake when you park the stroller.

Never leave your child unsupervised in the stroller.

Always use the safety harness when your child is in the stroller.

Do not inflate the tyres any more than 26 PSI.

Do not use the seat for any other stroller models.

Do not use the carry cot once your child can sit up unaided.

Make sure children are clear of any moving parts when adjusting the stroller, otherwise they may be injured.

Use the safety strap located on the handle at all times.

The harness can form loops which may be a strangulation hazard.

Never leave a harness connected when not fitted to a child in the stroller.

To avoid serious injury always use the harness provided to secure your child. Always adjust the straps to suit the size of your child's body. It is unsafe to use accessories other than those supplied by Edwards & Co.

Care should be taken whilst folding and unfolding the stroller to prevent fingers being trapped.

This stroller is suitable for one child only. Do not carry extra children or bags on this stroller.

The parking brake must be applied when taking your child in or out.

Do not place heavy weights on the handle of the stroller as it will impact the stability of the frame.

We recommend you take your child out of the stroller when ascending or descending stairs.

When installing the carry cot, seat unit or capsule in the stroller, ensure it is locked in place before use.

Keep away from fire and extreme heat.

We do not recommend using the stroller when jogging.

# Stroller Components



Oscar stroller frame



Otis stroller frame



Seat unit



Car seat capsule



Carry cot

## Unfolding the stroller

Place the frame flat on the ground with the handle facing upwards as pictured.



Lift the black clip (as indicated in the picture) located on the right hand side of the frame away from the catch clip and pull the handle of the stroller upwards.

The stroller will unfold and CLICK into place.

## Rear wheel installation and removal



To insert the wheel, simply insert the rod on the wheel hole located on each wheel strut until you hear a CLICK.



To remove the wheel, push down the metal lever (as pictured) and pull the wheel outwards simultaneously.

## Front wheel installation and removal

### OSCAR 3-WHEELER MODEL



To install the wheel, insert the wheel rod into the frame hole as pictured until you hear a CLICK.

To remove the wheel, push the level located at the top of the wheel hold inwards (towards the stroller) as indicated by the arrow.

### OTIS 4-WHEELER MODEL



To install the wheel, insert the wheel rod into the frame hole as pictured until you hear a CLICK.

To remove the wheel, twist the release dial anti-clockwise as indicated.

## Locking the front wheels

### OSCAR 3-WHEELER MODEL



The swivel lock is located at the top of the handel on the right hand side of the stroller.

To lock the wheel swivel, press the small button located on the outside of the lock, and simultaneously lower the lever until you hear a **CLICK**. This locks the swivel and holds the wheel in a straight position.

To free the wheel, raise the lever upwards until you hear a **CLICK**.

### OTIS 4-WHEELER MODEL



To lock the swivel on the front wheels, slide the lever downwards.

To unlock the swivel, slide the lever upwards.

## Fixing the parking brake



To engage the brake, push the red lever located on the right hand wheel strut downwards. This brake locks both rear wheels.

Then release the brake, lift the lever upwards.

## Installing and removing the seat unit



To install the seat unit, insert the locking adaptors into the frame as pictured and push downwards (do not press the release button when installing).

**Warning** – ensure the seat unit is locked into the stroller frame before use.

To remove the seat unit, press the two release buttons at the same time and lift upwards (as pictured).

**Note** – the seat unit can be installed in a front-facing, and a rear-facing position.

## Installing and removing the Edwards & Co car seat capsule (*optional accessory*)



To install the capsule, with the handle upright insert the capsule locking adaptors into the frame as pictured and push downwards firmly. The capsule must be in a rear-facing position.



To lock the capsule in place, press the two buttons behind the handle hinge and push the handle forwards as pictured.

**Warning** – ensure the capsule is locked into the stroller frame before use.

To remove the capsule, press the buttons behind the handle hinge and move the handle back in an upright position. The capsule should lift out freely.

## Installing and removing the Edwards & Co carry cot (*optional accessory*)



To install the carry cot insert the capsule locking adaptors into the frame as pictured and push downwards firmly. The cot must be fitted in a rear facing position.

**Warning** – ensure the cot is locked into the stroller frame before use.



To remove the carry cot, lift the flap located at the front of the carry cot as pictured and lift the carry cot upwards.



## Seat recline adjustment



The seat unit has three recline positions – lie flat, recline and seated.

To adjust the recline, squeeze metal lever at the rear of the seat upwards and raise or lower the seat to the desired position.

## Installing and removing the bumper bar



To install the bumper bar, insert the rods on each end of the bar into the bumper bar retaining bracket as pictured until you hear a CLICK.

To remove the bar, press the release buttons located on the underside of the bumper bar retaining bracket.

## Handle height adjustment



To adjust the handle height, press the two buttons on the inside of the handle hinge and raise or lower as pictured.

## Leg rest height adjustment



To raise and lower the leg rest, press the button on both sides of the leg rest hinge as pictured until you hear it **CLICK** into position.

## Collapsing the stroller



Pull the two sliding levers just below the handle hinge (on the stroller frame) then push the handle downwards towards the floor.



For compact folding, fold the stroller with the seat unit removed or with the seat unit facing forwards. The collapsed stroller should look as pictured.

## **Locking and unlocking the seat harness**

To fit the harness, piece together the two right hand fittings together and CLICK into the buckle. Then piece together the two left hand fittings together and click into the buckle.

To remove the harness, press the large button on the front of the buckle until it releases.

## Care Tips

We recommend storing your stroller indoors to avoid corrosion.

We recommend regular inspection and maintenance of locking devices and security of essential components.

Regularly check all parts for wear and tear. Lubricate if tight.

Do not use spray lubricants.

The fabric is washable. To clean the liner we recommend sponging with warm soapy water and a mild detergent. A mild disinfectant may be used if desired.

Never clean with abrasive, ammonia-based, bleach-based or spirit-based cleaners.

If the wheels become damaged or worn discontinue use and replace.

Avoid sun exposure for long periods to prevent fading and damage to the fabric.

Avoid submersing the product in salt water. If you do expose it to salt water ensure you wash the frame, particularly moving parts, in cold fresh water.

**Edwards & Co strollers are manufactured and tested to the highest durability and quality standards. By following the care guidelines provided, your stroller will last for many years to come.**

## Warranty

All Edwards & Co products are guaranteed for one year from the date of purchase against defects in material and workmanship.

If we determine that the product has a manufacturing fault, we will repair or replace it free of charge to you. The decision to repair or replace is solely at the discretion of Edwards & Co.

Our manufacturing warranty excludes claims resulting from misuse, abnormal use, overloading, general wear and tear, child outgrowing product, not following instructions, transportation damage (including airline or freight damage), poorly maintained product, dropped goods, negligence, second-hand product, modified product, colour fading, over inflation, mould, damage to handle foam in use or fabric cuts and tears. Our warranty also does not cover tyre punctures or corrosion to frames or fasteners as a result of atmospheric or environmental conditions.

The warranty is "return to base" and not a free in-home service. This means the customer is responsible for any inwards freight charge to return product to an Edwards & Co representative for warranty or service.

## **Distributed by:**

Edwards & Co

PO Box 35-445

Browns Bay

Auckland 0630

## **Customer Care**

Email – [sales@edandcobaby.com](mailto:sales@edandcobaby.com)

Phone – (09) 270 3406